

## Panel

Diagonal Size	65
Type	60Hz LED BLU
Resolution	1920*1080 (Full HD)
Pixel Pitch(mm)	0.744(H) × 0.744(V)
Active Display Area(mm)	1428.48(H) x 803.52(V)
Brightness(Typ.)	400 nit
Contrast Ratio	4000:01:00
Viewing Angle(H/V)	178:178
Response Time(G-to-G)	6ms
Display Colors	10bit Dithering - 1.07Billion
Color Gamut	70%
Operation Hour	16/7

## Display

Dynamic C/R	Mega. DCR (AV Mode)
H-Scanning Frequency	30 ~ 81kHz
V-Scanning Frequency	48 ~ 75Hz
Maximum Pixel Frequency	148.5MHz

## Sound

Speaker Type	Built in Speaker(10W + 10W)
--------------	-----------------------------

## Connectivity

Input	
RGB	Analog D-SUB, DVI-D
Video	CVBS, Component, HDMI
Audio	Stereo mini Jack
Usb	USB Player
Output	
Audio	Stereo mini Jack
External Control	RS232C(in/out) thru stereo jack
External Sensor	Yes
Tuner	No

## Power

Type	Internal
Power Supply	AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
<b>Power Consumption</b>	
Max[W/h]	253
Typical[W/h]	180
BTU(Max)	862.73
Sleep mode	less than 0.5W
Off mode	less than 0.5W

## Mechanical Specification

Dimension (mm)	Set	1467.4x848x56.2
	Package	1600 x 980 x 287
Weight (kg)	Set	27.4
	Package	35.4
VESA Mount (mm)		400*400mm
Protection Glass		N/A
Stand Type		Foot Stand (Optional)
Media Player Option Type		N/A
Bezel Width (mm)		18.0mm(Bottom 23.5mm)

## Operation

<b>Operating Temperature</b>	0.0 °C ~ 40.0 °C	<b>Humidity</b>	10.0 % ~ 80.0 %
------------------------------	------------------	-----------------	-----------------

## Feature

<b>Key Features</b>		LED LFD
<b>Special Features</b>		Built in Speaker(10W + 10W), PIP/PBP, Narrow Bezel, Light Weight, RS232 In/Out 1 D-Sub & 1 HDMI, USB Player
Internal Player	Processor	N/A
	On-Chip Cache Memory	N/A
	Clock Speed	N/A
	Main Memory Interface	N/A
	Graphics	N/A
	Storage (FDM)	N/A
	Multimedia	N/A
	IO Ports	N/A
Operating System		N/A

## Certification

<b>Safety</b>	UL(USA) : cUL60950-1, CSA (Canada):cUL60950-1, TUV (Germany) : IEC60950-1/EN60950-1, NEMKO (Norway): IEC60950-1/EN60950-1, CB (Europe) : IEC60950-1/EN60950-1, KC (Korea) : K 60950-1, CCC (China) : GB4943.1-2011, PSB (Singapore ) : PSB+IEC60950-1 , EAC (Russia) : EAC+IEC60950-1 , NOM (Mexico ) : NOM-001-SCFI-1993 , IRAM (Argentina ) : IRAM+IEC60950-1 , SASO (Saudi Arabia ) :SASO+IEC60950-1, BIS(India) : IEC60950-1 / IS13252, INMETRO (Brazil):INMETRO+IEC60950-1, BSMI(Taiwan):BSMI+IEC60950-1, RCM
<b>EMC</b>	:EN55022:2006+A1:2007 EN55024:1998+A1:2001+A2:2003, VCCI (Japan): VCCI V-3 /2010.04 Class A , KCC/EK (Korea):KN13 / KN20, BSMI (Taiwan) : CNS13438 (ITE EMI) Class A / CNS13439 (AV EMI) / CNS14409 (AV EMS) / CNS14972 (Digital) , C-Tick (Australia) : AS/NZS CISPR22:2009 , CCC(China) :GB9254-2008 GB17625.1-2012 , GOST(Russia/CIS):GOST R 51317 Series,GOST 22505-97.EN55022:2006+A1:2007.EN55024:1998+A1:2001+A2:2003

## Accessory

<b>Included</b>		Quick Setup Guide, Warranty Card, D-Sub cable, Power Cord, Remote Controller, Batteries
<b>Optional</b>	<b>Stand</b>	STN-L6500E
	<b>Mount</b>	WMN6575SD
	<b>Specialty</b>	CML450D (Ceiling Mount)
	<b>Tray</b>	N/A

## Media Player

<b>Media Player</b>	SBB (Optional)
---------------------	----------------